

J31G/FS31G

H Tipi Gövdeli Yüksek Hızlı
Eksantrik Pres ve Besleme Hattı
*Punching Line of Straight Side
High-Speed Press*



Powermac®

Gücü hissedin | *Feel the power*



Başlıca Özellikleri

- Yüksek rijitlik ve düşük esneme sağlayan H tipi gövde yapısı
- Geniş tabla, koç tablası ve kolonlar arası açıklık sayesinde farklı ihtiyaçlara uygunluk
- Yüksek performansta darbe emici özellik sağlayan sağlam döküm koç
- Yüksek hassasiyet sağlayan 8 yüzeyli iğne rulmanlı koç kızakları
- Alt ölü noktasının hassasiyetini artıran, biyel kolu hidrolik kilitleme sistemi
- Rotary enkoder ve kullanım paneli

Main Structure Features

- Steel-welded and close-box frame, high rigidity and less deformation.
- Large-size table and slide, large distance between uprights, to ensure more convenient operation.
- High rigidity casting slide, ensuring the high performance of shock absorption.
- Eight-side rectangle guides and needle rollers for guiding of the slide in high precision.
- Hydraulic locking device for connecting rod, to enhance the precision of bottom dead center.
- Rotary encoder control and human machine interface system.

J31G/FS31G

H Tipi Gövdeli Beslemeli Yüksek
Hızlı Eksantrik Pres
Punching Line Of Straight Side
High-Speed Press

Powermac[®]

		Model									
		Birim Unit	J31G-80	J31G-80B	J31G-125	J31G-125B	J31G-160	J31G-160B	J31G-200	J31G-300	J31G-400
Nominal Basınç Nominal Pressure		kN	800		1.250		1.600		2.000	3.000	4.000
Max. Sac Kalınlığı Max. Sheet Thickness		mm	2		3		3		3	3	3
Strok Mesafesi Stroke of Slide		mm	30		30		30		30	30	30
Strok Sayısı Strokes		S.P.M.	160-280		160-240		160-220		150-200	100-160	100-130
Maks. Kalıp Seti Yüksekliği Max. Die Set Height		mm	360		400		400		400	450	450
Reglaj Ayarı Die Height Adjustment		mm	50		50		50		50	50	50
Kolonlar Arası Mesafe Distance Between Uprights	Genişlik L-R	mm	920	1.020	1.120		1.320		1.320	1.420	1.550
	Derinlik F-B	mm	380		450		520		550	750	750
Koç Tabla Ölçüsü Bottom Size of Slide	Genişlik L-R	mm	800	1.000	1.000		1.200		1.200	1.300	1.400
	Derinlik F-B	mm	450	650	550		600		600	900	900
Tabla Ölçüsü Size of Table	Genişlik L-R	mm	900	1.000	1.100		1.300		1.300	1.400	1.500
	Derinlik F-B	mm	500	750	600		700		800	1.000	1.000
Tabla Delik Ölçüsü Size of Opening in Table	Genişlik L-R	mm	700		880		1.000		1.000	1.000	1.000
	Derinlik F-B	mm	180		150		250		210	650	650
Motor gücü Motor Power		kW	11		18,5		22		30	37	45
Toplam Ağırlık Total Weight		kg	10.000		13.000		16.500		22.000	38.000	43.000



FORMSİTE

Endüstri Makinaları Pazarlama İth. İhr. San. ve Tic. Ltd. Şti.

2. Sanayi Sitesi 351 Sokak No:15 İZMİR - TÜRKİYE
Tel: (+90 232) 461 44 66 • (+90 232) 435 11 08
Faks: (+90 232) 486 36 71 • GSM: (+90 530) 645 51 73
www.formsite.com.tr info@formsite.com.tr

KOSGEB
www.kosgib.gov.tr
basım tarihi: 15 / 06 / 2012

CE

www.bia.com.tr